#### **Product datasheet**

#### **BAULINE**




#### BA3RE068MOSP840NG



## BAULINE G3 REC 679MM 2500 NW SP AND

#### Description:

Outdoor recessed structure model BAULINE G3 REC 679MM 2500 NW SP, LAMP brand. Made of silver anodized aluminum extrusion and end covers of aluminum injection lacquered in silver grey polyester, with AISI304 stainless steel frame and serigraphed tempered glass. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP67, IK10 protection rating. Insulation class I. Lifetime: 83.000 L90 B10



Finish: Anodized matte silver

**Dimensions**: 679 x 80 x 100 mm **Weight**: 3.302 g

Installation: Floor recessed

Recessing measures: 683 x 72 x 107 mm

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.972 lm
 % :
 4000

 Plum:
 16,2W
 CRI :
 80

 Efficacy:
 121 lm/w
 MacAdam:
 3

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 83.000 L90 B10 (Ta=25°C) Gear: Electronic

**Power:** 15,4W

#### Light output tolerance +/- 10%

























## **CUSTOM MADE OPTIONS:**



























#### **BAULINE**





## BA3RE068MOSP840NG


## BAULINE G3 REC 679MM 2500 NW SP AND

### **PHOTOMETRIC DATA:**

BA3RE068MOSP840NG η = 100% Imax = 8284 cd/klm UTE: 1,00T CIE: 0 0 0 0 100







## **Product datasheet**

## **BAULINE**



# ACCESORIES:

**Assembly** 



Product code: BUREBO0683

Description:

BAULINE ACC. REC BOX 683



Product code: BUREBO1272

Description:

BAULINE ACC. REC BOX 1272