Product datasheet

BAULINE


BA3SF065MOSP840NG



BAULINE G3 SUR 650MM 2500 NW SP AND

Description:

Outdoor suspended or mounted surface structure model BAULINE G3 SUR 650MM 2500 NW SP, LAMP brand. Made of silver anodized aluminum extrusion and end covers of lacquered aluminum injection lacquered in silver grey polyester, with decorative frontal piece of silver serigraph polycarbonate. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP67, IK10 protection rating. Insulation class I. Lifetime: 83.000 L90 B10



Finish:Anodized matte silverDimensions:650 x 50 x 95 mm

x 50 x 95 mm

Weight: 2.252 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

| Light output: | 1.937 lm | ⁰K : | 4000 |
|---------------|--------------------------|---------------|------------------|
| Plum: | 16,2W | CRI : | 80 |
| Efficacy: | 119,6 lm/w | MacAdam: | 3 |
| Туре: | HIGH POWER LED | Power Supply: | 220-240V 50/60Hz |
| LED Lifetime: | 83.000 L90 B10 (Ta=25ºC) | Gear: | Electronic |
| Power: | 15,4W | | |

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light


Product datasheet

BAULINE

BA3SF065MOSP840NG

BAULINE G3 SUR 650MM 2500 NW SP AND





Worktitude for light

Product datasheet

BAULINE

ACCESORIES :

Support



Product code: WAAR120G

Description: ACC. ADJ WALL ARM 120 GR.



Product code: WAAR380G

Description:

ACC. ADJ WALL ARM 380 GR.

Worktitude for light