Product datasheet

DOMO 220




DO2RD40SY840DW



DOMO 220 G2 4000 NW DALI

Description:

Round recessed DOMO 220 G2 4000 downlight, LAMP brand. With external ring in white lacquered die-cast aluminium. Model for MID-POWER LED, 4000K colour temperature and control DALI gear included. Reflector designed by the optical concept named REDIL (Direct Emission LED Reflector), which consists of a two-phase reflection. Insulation class II.



Finish: Matte white RAL 9010

Weight: 1.508 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 3.812 lm
 °K:
 4000

 Plum:
 40,5W
 CRI:
 80

 Efficacy:
 94,1 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 120-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 37W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:



























DOMO 220






PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed
1	1,40	2924	1692
2	2,80	731	423
3	4,20	325	188
4	5,59	183	106

DOMO 220



ACCESORIES:

Optical



Product code:

8606130

Description:

DOMO 220 G2 ACC. INT OPAL DIFFUSER



Product code:

Description:

DIOPRD240G DOMO 220 ACC. OPAL GLASS GR.
DIOPRD240W DOMO 220 ACC. OPAL GLASS WH.



Product code:

Description:

DITRRD240B DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

DITRRD240G DOMO 220/KOMBIC ACC.TRANSP GLASS GR.

DITRRD240W DOMO 220/KOMBIC ACC.TRANSP GLASS WH.



Product code: RIRD240B Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

Description:

RIRD240G DOMO 220/KOMBIC ACC. DECO RING GR.
RIRD240W DOMO 220/KOMBIC ACC. DECO RING WH.

DOMO 220



