
Product datasheet

SHOT 80

MC209SP840NG





SHOT 80 G2 900 NW SP GR.

Description:

Outdoor spotlight model SHOT 80 G2 900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Texturised grey


Weight: 1.324 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	720 lm	⁰K :	4000	
Plum:	9,4W	CRI :	80	
Efficacy:	76,6 lm/w	MacAdam:	3	
Туре:	HIGH POWER LED	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	60.000 L90 B10 (Ta=25⁰C)	Gear:	Electronic	
Power:	6W			

Light output tolerance +/- 10%



Worktitude for light

SHOT 80

MC209SP840NG

SHOT 80 G2 900 NW SP GR.



PHOTOMETRIC DATA :

MC209SP840NG	180°	alpha = 19,9°	H (m)	D (m)	Emax	Emed
η = 100%		\wedge	1	0,35	4402	3175
lmax = 6135 cd/klm		/ \				
UTE:	90° 90°		2	0,70	1101	794
CIE: 99 100 100 100 100						
			3	1,05	489	353
	O °		4	1,41	275	198

Product datasheet

SHOT 80

ACCESORIES :

Assembly



Product code: MCSPM Description: SHOT 80 G2 ACC. SPIKE

ACCESORIES :

Optical



Product code: MCSC82B Description: SHOT 80 G2 ACC. ANTIGLARE SCREEN Worktitude for light