Product datasheet


MUN LIGHT

ML1480SF25830NB

MUN LIGHT SUR Ø480 2500 WW GRH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 4.534 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.181 lm °K: 3000 Plum: 23,2W CRI: 80 Efficacy: 94 lm/w MacAdam: <3

Type: LOW POWER OSRAM Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

20W Power:

Gear: Electronic





























CUSTOM MADE OPTIONS:






















MUN LIGHT




ML1480SF25830NB

MUN LIGHT SUR Ø480 2500 WW GRH.

PHOTOMETRIC DATA:





alpha = 114,5°	H (m)	D (m)	Emax	Emed
	1	3,11	745	214
	2	6,22	186	54
	3	9,33	83	24
	4	12,44	47	13