Product datasheet

MUN LIGHT


ML1480SF40840NB



MUN LIGHT SUR Ø480 4000 NW GRH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 4.534 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 4.317 lm °K: 4000 Plum: 61,9W CRI: 80 Efficacy: 69,7 lm/w MacAdam: <3

Type: MID POWER OSRAM Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

59W Power:

Gear: Electronic



















CUSTOM MADE OPTIONS:






















MUN LIGHT





PHOTOMETRIC DATA:

10540032 η = 100% Imax = 344 cd/klm UTE: 1,00E + 0,00T CIE: 47 79 96 100 100



alpha = 114,4°	H (m)
	1
	2
	3
	4

_					
	H (m)	D (m)	Emax	Emed	
	1	3,10	1484	428	
	2	6,21	371	107	
	3	9,31	165	48	
	4	12,41	93	27	