Product datasheet

MUN LIGHT




10540012



MUN LIGHT SUR Ø480 2500 NW GRH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480 2500 NW GRH., LAMP brand. Made of graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with neutral white color temperature and control gear included. IP20 protection rating. Insulation class I.



Finish: Texturised matte graphite RAL 7021

Weight: 6.800 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.181 lm
 °K:
 4000

 Plum:
 23,2W
 CRI:
 80

 Efficacy:
 94 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER OSRAM Power Supply: 220-240V 50/60Hz

Gear:

Electronic

LED Lifetime: 50.000 L80 B10

Power: 20W

Light output tolerance +/- 10%

AI
















MUN LIGHT




10540012

MUN LIGHT SUR Ø480 2500 NW GRH.

PHOTOMETRIC DATA:





alpha = 114,5°	H (m)	D (m)	Emax	Emed
	1	3,11	745	214
	2	6,22	186	54
	3	9,33	83	24
	4	12,44	47	13