Product datasheet

MUN LIGHT

10540032





MUN LIGHT SUR Ø480 4000 NW GRH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480 4000 NW GRH., LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with neutral white color temperature and control gear included. IP20 protection rating. Insulation class I.



Texturised matte graphite RAL 7021 Finish: Weight: 6.800 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	4.317 lm	⁰K :	4000	
Plum:	61,9W	CRI :	80	
Efficacy:	69,7 lm/w	MacAdam:	<3	
Туре:	MID POWER OSRAM	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	50.000 L80 B10	Gear:	Electronic	
Power:	59W			

Light output tolerance +/- 10%



Worktitude for light

MUN LIGHT

10540032

MUN LIGHT SUR Ø480 4000 NW GRH.



PHOTOMETRIC DATA :

10540032	180°	alpha = 114,4°	H (m)	D (m)	Emax	Emed
η = 100%			1	3,10	1484	428
lmax = 344 cd/klm						
UTE: 1,00E + 0,00T	90° 90°		2	6,21	371	107
CIE: 47 79 96 100 100						
			3	9,31	165	48
	0°		4	12,41	93	27