MUN LIGHT

10540092

MUN LIGHT SUS Ø300 1000 NW GRH.

Description:

Round suspended downlight model MUN LIGHT SUS Ø300 1000 NW GRH., LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with neutral white color temperature and control gear included. IP20 protection rating. Insulation class I.



Finish: Texturised matte graphite RAL 7021 Weight: 2.680 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	716 lm	⁰K :	4000	
Plum:	9,3W	CRI :	80	
Efficacy:	77 lm/w	MacAdam:	<3	
Туре:	LOW POWER OSRAM	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	50.000 L80 B10	Gear:	Electronic	
Power:	8W			

Light output tolerance +/- 10%



Worktitude for light

MUN LIGHT

10540092

MUN LIGHT SUS Ø300 1000 NW GRH.



10540092	180°	alpha = 115,2°	H (m)	D (m)	Emax	Emed
η = 100% Imax = 342 cd/klm			1	3,15	245	70
UTE: 1,00E + 0,00T	90° 90°		2	6,30	61	17
CIE: 46 79 96 100 100			3	9,45	27	8
	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		4	12,59	15	4
	0°		- <b>f</b>	.2,00	10	-

Worktitude for light