Product datasheet

FIL 50

14740523



FIL LED G2 OPAL REC 6000 NW GR.

Description:

Recessed luminaire model FIL LED G2 OPAL REC 6000 NW GR., LAMP brand. Made of satin grey painted extruded aluminium with opal polycarbonate diffuser. Model for MID-POWER LED, neutral white colour temperature and control gear included. With opal polycarbonate diffuser. With a IP42, IK07 protection rating. Insulation class I. Photobiological safety group 0.



Finish: Gloss grey

1.137 x 66 x 67 mm Dimensions: Weight: 2.166 g

Installation: Recessed

Recessing measures: 1,147 x 52 x 80 mm

TECHNICAL SPECIFICATIONS:

Light output: 3.761 lm °K: 4000 Plum: 40,6W CRI: 80 Efficacy: 92,6 lm/w MacAdam: 3

Type: MID POWER TRIDONIC Power Supply: 220-240V 50/60Hz

LED Lifetime: 50000 L70 B10 Gear: Electronic

37W Power:

Light output tolerance +/- 10%

































14740523



FIL LED G2 OPAL REC 6000 NW GR.

PHOTOMETRIC DATA:





alpha = 101,7°	H (m)	D (m)	Emax	Emed
	1	2,46	1447	526
	2	4,92	362	132
	3	7,37	161	58
	4	9,83	90	33

Product datasheet

FIL 50



ACCESORIES:

Assembly



Product code: Description:

4700580 FIL ACC. REC PROFILE X/MM WH.
4700583 FIL ACC. REC PROFILE X/MM GR.
4705100 FIL ACC. COVER X/MM WH.
4705103 FIL ACC. COVER X/MM GR.



Product code:

4705210 FIL ACC. REC 90° CORNER WH.
 4705213 FIL ACC. REC 90° CORNER GR.

Description:



Product code:

4706450 FIL ACC. REC END COVER WH. 4706453 FIL ACC. REC END COVER GR.

Description:



Product code:

9600990

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

Description:

9606010 ACC. INTM JOINT B

ACCESORIES:

Optical



Product code:

Description:

4700590 FIL ACC. OPAL DIFFUSER X/MM