#### **Product datasheet**

#### **DOMO TRIMLESS**




#### 10041110



#### **DOMO 220 G2 TRIM 3000 WW**

#### Description:

Round recessed DOMO 220 G2 TRIM 3000 WW downlight, LAMP brand. For trimless installation, without frame. Model for MID-POWER LED, warm white colour temperature and control gear included. Reflector designed by the optical concept named REDIL® (Direct Emission LED Reflector), which consists of a two-phase reflection. Insulation class II.



Finish: Matte white RAL 9010

Weight: 1.242 g

Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.825 lm
 % :
 3000

 Plum:
 32W
 CRI :
 80

 Efficacy:
 88,3 lm/w
 MacAdam:
 3

Type: MID POWER NICHIA Power Supply: 120-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 Gear: Electronic

Power: 29W

#### Light output tolerance +/- 10%



















Tel. +34937366800 Web www.lamp.es


# **DOMO TRIMLESS**





10041110

### **DOMO 220 G2 TRIM 3000 WW**

#### **PHOTOMETRIC DATA:**







H (m)	D (m)	Emax	Emed
1	1,38	2176	1270
2	2,76	544	318
3	4,13	242	141
4	5,51	136	79

Data according to regulations 2019/2020/EU and 2019/2015/EU

### **Product datasheet**

## **DOMO TRIMLESS**



ACCESORIES:

Optical



Product code: Description:

8606130 DOMO 220 G2 ACC. INT OPAL DIFFUSER