Product datasheet

STORMBELL




10441001



STORMBELL 3000 WW FL WH.

Description:

Suspended downlight model STORMBELL 3000 WW FL WH., LAMP brand. Made of shiny white extruded and injected aluminium body. Model for COB with warm white colour temperature and control gear included on shiny white decorative rose. Flood aluminium reflector. Insulation class I.



Shiny white RAL 9010 Finish:

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.402 lm °K: 3000 Plum: 26,3W CRI: 80 Efficacy: 91,3 lm/w MacAdam: <3

Type: COB CITIZEN Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 Gear: Electronic

25W Power:

Light output tolerance +/- 10%

CLASE AI 20














STORMBELL




10441001

STORMBELL 3000 WW FL WH.

PHOTOMETRIC DATA:





alpha = 39,0°	H (m)	D (m)	Emax	Emed
	1	0,71	4778	3160
	2	1,42	1195	790
	3	2,12	531	351
	4	2,83	299	198

STORMBELL



ACCESORIES:

Optical



Product code:

10400100



STORMBELL ACC. BELL WH.



Product code:

10400102

Description:

STORMBELL ACC. BELL BK.



Product code:

10400120

Description:

STORMBELL ACC. BELL OPAL



Product code:

10400132

Description:

STORMBELL ACC. HONEYCOMB GRILLE



Product code:

10400140

Description:

STORMBELL ACC. TRANS GLASS



Product code:

10400150

Description:

STORMBELL ACC. OPAL GLASS