Product datasheet

STORMBELL




10441021



STORMBELL 5000 WW FL WH.

Description:

Suspended downlight model STORMBELL 5000 WW FL WH., LAMP brand. Made of shiny white extruded and injected aluminium body. Model for COB with warm white colour temperature and control gear included on shiny white decorative rose. Flood aluminium reflector. Insulation class I.



Shiny white RAL 9010 Finish:

Weight: 4.592 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 3.690 Im °K: 3000 Plum: 47,4W CRI: 80 Efficacy: 77,8 lm/w MacAdam: <3

Type: COB CITIZEN Power Supply: 100-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 Gear: Electronic

44W Power:

Light output tolerance +/- 10%

CLASE LED AI 20












STORMBELL




10441021

STORMBELL 5000 WW FL WH.

PHOTOMETRIC DATA:





alpha = 39,2°	H (m)	D (m)	Emax	Emed
	1	0,71	7336	4849
	2	1,42	1834	1212
	3	2,14	815	539
	4	2,85	459	303

STORMBELL



ACCESORIES:

Optical



Product code:

10400100



STORMBELL ACC. BELL WH.



Product code:

10400102

Description:

STORMBELL ACC. BELL BK.



Product code:

10400120

Description:

STORMBELL ACC. BELL OPAL



Product code:

10400132

Description:

STORMBELL ACC. HONEYCOMB GRILLE



Product code:

10400140

Description:

STORMBELL ACC. TRANS GLASS



Product code:

10400150

Description:

STORMBELL ACC. OPAL GLASS