Product datasheet

MUN LIGHT

Worktitude for light


10540010



MUN LIGHT SUR Ø480 2500 NW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480 2500 NW WH., LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with neutral white color temperature and control gear included. IP20 protection rating. Insulation class I.



Finish: Texturised matte white RAL 9016

Weight: 6.800 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.311 lm
 °K :
 4000

 Plum:
 23,2W
 CRI :
 80

 Efficacy:
 99,6 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER OSRAM Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10

Power: 20W

Gear: Electronic

Light output tolerance +/- 10%




















MUN LIGHT




10540010

MUN LIGHT SUR Ø480 2500 NW WH.

PHOTOMETRIC DATA:





alpha = 114,5°	H (m)	D (m)	Emax	Emed
	1	3,11	790	227
	2	6,22	198	57
	3	9,33	88	25
	4	12,44	49	14