Product datasheet

MUN LIGHT




10540070



MUN LIGHT SUS Ø480 2500 NW WH.

Description:

Round suspended downlight model MUN LIGHT SUS Ø480 2500 NW WH., LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with neutral white color temperature and control gear included. IP20 protection rating. Insulation class I.



Finish: Texturised matte white RAL 9016

Weight: 6.000 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 2.311 lm
 °K:
 4000

 Plum:
 23,2W
 CRI:
 80

 Efficacy:
 99,6 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER OSRAM Power Supply: 220-240V 50/60Hz

Electronic

LED Lifetime: 50.000 L80 B10 Gear:

Power: 20W

Light output tolerance +/- 10%
















MUN LIGHT




10540070

MUN LIGHT SUS Ø480 2500 NW WH.

PHOTOMETRIC DATA:





alpha = 114,5°	H (m)	D (m)	Emax	Emed
	1	3,11	790	227
	2	6,22	198	57
	3	9,33	88	25
	4	12,44	49	14