Product datasheet

MUN LIGHT

Worktitude for light


10541060



MUN LIGHT SUS Ø480 4000 WW WH.

Description:

Round suspended downlight model MUN LIGHT SUS Ø480 4000 WW WH., LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with warm white color temperature and control gear included. IP20 protection rating. Insulation class I.



Finish: Texturised matte white RAL 9016

Weight: 6.000 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 4.576 lm
 %K:
 3000

 Plum:
 61,9W
 CRI:
 80

 Efficacy:
 73,9 lm/w
 MacAdam:
 <3</td>

Type: MID POWER OSRAM Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 Gear: Electronic

Power: 59W

Light output tolerance +/- 10%




















MUN LIGHT




10541060

MUN LIGHT SUS Ø480 4000 WW WH.

PHOTOMETRIC DATA:





alpha = 114,4°	H (m)	D (m)	Emax	Emed
	1	3,10	1573	453
	2	6,21	393	113
	3	9,31	175	50
	4	12,41	98	28