Product datasheet

FIL 50



14740503



FIL LED G2 OPAL REC 3000 NW GR.

Description:

Recessed luminaire model FIL LED G2 OPAL REC 3000 NW GR., LAMP brand. Made of satin grey painted extruded aluminium with opal polycarbonate diffuser. Model for MID-POWER LED, neutral white colour temperature and control gear included. With opal polycarbonate diffuser. With a IP42, IK07 protection rating. Insulation class I. Photobiological safety group 0.



Finish: Gloss grey

1.137 x 66 x 67 mm Dimensions: Weight: 2.166 g

Installation: Recessed

Recessing measures: 1,147 x 52 x 80 mm

TECHNICAL SPECIFICATIONS:

Light output: 2.004 Im °K: 4000 Plum: 21,3W CRI: 80 Efficacy: 94,1 lm/w MacAdam: 3

Type: MID POWER TRIDONIC Power Supply: 220-240V 50/60Hz

LED Lifetime: 50000 L80 B10 Gear:

19W Power:

Light output tolerance +/- 10%































Electronic


FIL 50






FIL LED G2 OPAL REC 3000 NW GR.

PHOTOMETRIC DATA:





alpha = 102,7°	H (m)	D (m)	Emax	Emed
	1	2,50	760	272
	2	5,00	190	68
	3	7,50	84	30
	4	10,00	48	17

Product datasheet

FIL 50



ACCESORIES:

Assembly



Product code: Description:

4700580 FIL ACC. REC PROFILE X/MM WH.
4700583 FIL ACC. REC PROFILE X/MM GR.
4705100 FIL ACC. COVER X/MM WH.
4705103 FIL ACC. COVER X/MM GR.



Product code:

4705210 FIL ACC. REC 90° CORNER WH.
 4705213 FIL ACC. REC 90° CORNER GR.

Description:



Product code:

4706450 FIL ACC. REC END COVER WH. 4706453 FIL ACC. REC END COVER GR.

Description:



Product code:

9600990

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

Description:

9606010 ACC. INTM JOINT B

ACCESORIES:

Optical



Product code:

Description:

4700590 FIL ACC. OPAL DIFFUSER X/MM