Product datasheet

FIL 50

14740573



FIL LED G2 PRISM REC 6000 NW GR.

Description:

Recessed luminaire model FIL LED G2 PRISM REC 6000 NW GR., LAMP brand. Made of satin grey painted extruded aluminium with prismatic polycarbonate diffuser. Model for MID-POWER LED, neutral white colour temperature and control gear included. Glare rating <19 (for 4h, 8h 70/50/20). With a IP42, IK07 protection rating. Insulation class I. Photobiological safety group 0.



Finish: Gloss grey

1.137 x 66 x 67 mm Dimensions: Weight: 2.166 g

Installation: Recessed

Recessing measures: 1,147 x 52 x 80 mm

TECHNICAL SPECIFICATIONS:

Light output: 3.942 lm °K: 4000 Plum: 40,6W CRI: 80 Efficacy: 97,1 lm/w MacAdam: 3

Type: MID POWER TRIDONIC Power Supply: 220-240V 50/60Hz

LED Lifetime: 50000 L70 B10 Gear: Electronic

37W Power:

Light output tolerance +/- 10%


































14740573




FIL LED G2 PRISM REC 6000 NW GR.

PHOTOMETRIC DATA:

14740573 $_{\eta}$ = 100% Imax = 617 cd/klm UTE: 1,00B Imax CIE: 75 96 99 100 100





| | H (m) | D (m) | Emax | Emed |
|---|-------|-------|------|------|
| | 1 | 1,31 | 2403 | 1696 |
| | 2 | 2,62 | 601 | 424 |
| | 3 | 3,93 | 267 | 188 |
| 1 | 4 | 5,24 | 150 | 106 |

Product datasheet

FIL 50



ACCESORIES:

Assembly



| Prod | luct | cod | le: | |
|------|------|-----|-----|--|
|------|------|-----|-----|--|

4700580 FIL ACC. REC PROFILE X/MM WH. 4700583 FIL ACC. REC PROFILE X/MM GR. 4705100 FIL ACC. COVER X/MM WH. FIL ACC. COVER X/MM GR. 4705103

Description:



Product code:

4705210 4705213

Description:

FIL ACC. REC 90° CORNER WH. FIL ACC. REC 90° CORNER GR.



Product code:

4706450 FIL ACC. REC END COVER WH. 4706453 FIL ACC. REC END COVER GR.

Description:



Product code:

9600990

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

Description: ACC. INTM JOINT B

Tel.

+34937366800