Product datasheet

FIL 50

Worktitude for light

14741513



FIL LED G2 OPAL REC 4600 WW GR.

Description:

Recessed luminaire model FIL LED G2 OPAL REC 4600 WW GR., LAMP brand. Made of satin grey painted extruded aluminium with opal polycarbonate diffuser. Model for MID-POWER LED, warm white colour temperature and control gear included. With opal polycarbonate diffuser. With a IP42, IK07 protection rating. Insulation class I. Photobiological safety group 0.



Finish: Gloss grey

Dimensions: 1.700 x 66 x 67 mm **Weight:** 2.860 g

Installation: Recessed

Recessing measures: 1,710 x 52 x 80 mm

TECHNICAL SPECIFICATIONS:

 Light output:
 2.850 lm
 %K:
 3000

 Plum:
 31,2W
 CRI:
 80

 Efficacy:
 91,3 lm/w
 MacAdam:
 3

Type: MID POWER TRIDONIC Power Supply: 220-240V 50/60Hz

LED Lifetime: 50000 L80 B10 Gear: Electronic

Power: 28W

Light output tolerance +/- 10%

























14741513



FIL LED G2 OPAL REC 4600 WW GR.

PHOTOMETRIC DATA:





alpha = 102,7°	H (m)	D (m)	Emax	Emed
	1	2,50	1082	387
	2	5,00	271	97
	3	7,50	120	43
	4	10,00	68	24

Product datasheet

FIL 50



ACCESORIES:

Assembly



Product code: Description:

4700580 FIL ACC. REC PROFILE X/MM WH.
4700583 FIL ACC. REC PROFILE X/MM GR.
4705100 FIL ACC. COVER X/MM WH.
4705103 FIL ACC. COVER X/MM GR.



Product code:

4705210 FIL ACC. REC 90° CORNER WH.
 4705213 FIL ACC. REC 90° CORNER GR.

Description:



Product code:

4706450 FIL ACC. REC END COVER WH. 4706453 FIL ACC. REC END COVER GR.

Description:



Product code:

9600990

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

Description:

9606010 ACC. INTM JOINT B

ACCESORIES:

Optical



Product code:

Description:

4700590 FIL ACC. OPAL DIFFUSER X/MM