Product datasheet

FIL 70


4740693



FIL + LED OPAL REC 2600 NW GR.

Description:

Recessed mounted structure model FIL + LED OPAL REC 2600 NW GR., LAMP brand. Made of satin grey lacquered extruded aluminium and with opal diffuser. Model for MID-POWER LED, with neutral white colour temperature and electronic control gear included. IP42, IK06 protection rating. Insulation class I. Photobiological safety group 0.



Finish: Gloss grey

1.162 x 89 x 70 mm Dimensions: Weight: 2.662 g

Installation: Recessed

Recessing measures: 1,174 x 78 x 85 mm

TECHNICAL SPECIFICATIONS:

Light output: 2.143 lm °K: 4000 Plum: 19,2W CRI: 80 Efficacy: 111,6 lm/w MacAdam: 3

Type: MID POWER PHILIPS Power Supply: 220-240V 50/60Hz

60.000 L80 B10 LED Lifetime: Gear: Electronic

17W Power:

Light output tolerance +/- 10%










































Worktitude for light

PHOTOMETRIC DATA:








Product datasheet

FIL 70



ACCESORIES:

Assembly



Product code:

4700120 4700123

Description:

FIL + ACC. REC 90° CORNER WH. FIL + ACC. REC 90° CORNER GR.



Product code:

4700390 4700393

Description:

FIL + ACC. COVER X/MM WH.
FIL + ACC. COVER X/MM GR.



Product code:

4700490 4700493

Description:

FIL + ACC. REC PROFILE X/MM WH. FIL + ACC. REC PROFILE X/MM GR.



Product code:

4700680 4700683

Description:

FIL + ACC. REC END COVER WH. FIL + ACC. REC END COVER GR.



Product code:

4806043

Description:

ACC. INTM JOINT



Product code:

9600990

Description:

ACC. ELECTROSTATICS WRIST STRAP

ACCESORIES:

Optical



Product code:

Description:

4700400 FIL + ACC. OPAL DIFFUSER X/MM

FIL 70



