Product datasheet

TRACE 65

Worktitude for light


5641502



TRACE IP65 100 HOR 70 WW BK.

Description:

Outdoor wall-recessed luminaire model TRACE IP65 100 HOR 70 WW BK., LAMP brand. Body made of injected aluminium and matt black serigraphed tempered glass. Model for MID-POWER LED with warm white colour temperature and control gear included. Texturised white lacquered aluminium symmetric reflector. IP65, IK07 protection rating. Insulation class I.



Finish: CATAPHORESIS

Weight: 672 g

Installation: Wall recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 68 lm
 $^{\circ}$ K:
 3000

 Plum:
 2,7W
 CRI:
 80

 Efficacy:
 25 lm/w
 MacAdam:
 <3</td>

Type: MID POWER OSRAM Power Supply: 100-240V 50/60Hz

LED Lifetime: 100.000 L90 B10 Gear: Electronic

Power: 1.5W

Light output tolerance +/- 10%



















TRACE 65





5641502

TRACE IP65 100 HOR 70 WW BK.

PHOTOMETRIC DATA:

5641502 η = 100% Imax = 337 cd/klm UTE: 0,50T





alpha = 600,0°	H (m)	D (m)	Emax	Emed
	1	0,00	-1	NAN
	2	0,00	0	NAN
	3	0,00	0	NAN
	4	0,00	0	NAN

Product datasheet

TRACE 65



ACCESORIES:

Assembly



Product code: Description:

5600723 TRACE IP65 ACC. 100 REC BOX