#### **Product datasheet**

#### **OWL**

# LAMP Worktitude for light


### 6941513



### **OWL CL.I 12500 NW GR.**

### Description:

Street luminaire model OWL CL.I 12500 NW GR., LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HI-POWER LED, neutral white color temperature and control gear included. With street optics. IP66, IK07 protection rating. Insulation class I. Its ball joint allows swiveling the light between 10° and -10°.



Finish: Texturised grey

Weight: 6.960 g

Maximum surface exposed to wind: 0.19 M2

Installation: Integrated in light-pole

### **TECHNICAL SPECIFICATIONS:**

 Light output:
 11.228 lm
 ⁰K:
 4000

 Plum:
 94,5W
 CRI:
 70

 Efficacy:
 118,8 lm/w
 MacAdam:
 4

Type: HI POWER OSRAM Power Supply: 198-265V 50/60Hz

LED Lifetime: 100.000 L90 B10 Gear: Electronic

Power: 87W

#### Light output tolerance +/- 10%



















# **OWL**







# 6941513

# **OWL CL.I 12500 NW GR.**

# PHOTOMETRIC DATA:





alpha = 139,3°	H (m)	D (m)	Emax	Emed
	1	5,39	4370	469
	2	10,78	1093	117
	3	16,17	486	52
	4	21,56	273	29

# **Product datasheet**

# **OWL**



ACCESORIES:

Support



Product code:

Description:

9607343 OWL ACC.WALL ARM 1M GR.