Product datasheet

MAUI SUSPENDED




7341341



MAUI SUS 1600 WW YE.

Description:

Tilting suspended downlight model MAUI SUS 1600 WW YE., LAMP brand. Made of texturised yellow lacquered injected aluminum. Model for HI-POWER LED with warm white colour temperature and control gear included inside the rose. Chromed optical assembly consists of non-flush reflectors for high visual comfort. Insulation class II.



Finish: 1021 textured

Weight: 1.350 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 867 lm
 ⁰K :
 3000

 Plum:
 24W
 CRI :
 80

Efficacy: 36,1 lm/w

Type: HI POWER CREE MacAdam: 4

LED Lifetime: 50.000 L90 B10 **Power Supply**: 220-240V 50/60Hz

Power: 19W **Gear:** Electronic

Light output tolerance +/- 10%




















MAUI SUSPENDED




7341341

MAUI SUS 1600 WW YE.

PHOTOMETRIC DATA:





alpha = 16,3°	H (m)	D (m)	Emax	Emed
\wedge	1	0,29	3557	2303
	2	0,57	889	576
	3	0,86	395	256
	4	1,14	222	144

MAUI SUSPENDED



