Product datasheet

MAUI SUSPENDED




7341343



MAUI SUS 1600 WW CRM.

Description:

Tilting suspended downlight model MAUI SUS 1600 WW CRM., LAMP brand. Made of texturised chrome lacquered injected aluminum. Model for HI-POWER LED with warm white colour temperature and control gear included inside the rose. Chromed optical assembly consists of non-flush reflectors for high visual comfort. Insulation class II.



Finish: Gloss grey + Alodine 1500

Weight: 1.350 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 867 lm °K: 3000 Plum: 24W CRI: 80

Efficacy: 36,1 lm/w

Type: HI POWER CREE MacAdam:

LED Lifetime: 50.000 L90 B10 Power Supply: 220-240V 50/60Hz

19W Gear: Power: Electronic

Light output tolerance +/- 10%





















Tel.


MAUI SUSPENDED




7341343

MAUI SUS 1600 WW CRM.

PHOTOMETRIC DATA:





alpha = 16,3°	H (m)	D (m)	Emax	Emed
\wedge	1	0,29	3557	2303
	2	0,57	889	576
	3	0,86	395	256
	4	1,14	222	144

MAUI SUSPENDED



