#### **Product datasheet**

#### NIU

# LAMP Worktitude for light


#### 8141523



# NIU LED RSYM CL.II 4500 GR.

#### Description:

Urban luminaire NIU LED RSYM CL.II 4500 GR., LAMP brand. Made of texturised grey lacquered aluminium injection and flat tempered serigraphed glass. Model for HI-POWER LED with neutral white colour temperature and control gear included. With rotosymmetrical micro-reflectors. IP66, IK10 protection rating. Insulation class II. Includes architectural arm, to adapt to Ø60mm.



Finish: Texturised grey

Weight: 16.600 g

Maximum surface exposed to wind: 0.18 M2

Installation: Integrated in light-pole

# **TECHNICAL SPECIFICATIONS:**

 Light output:
 4.068 lm
 °K:
 4000

 Plum:
 52W
 CRI:
 70

Efficacy: 78,2 lm/w

Type: HI POWER CREE MacAdam: 4

**LED Lifetime**: 50.000 L90 **Power Supply**: 220-240V 50/60Hz

Power: 48W Gear: Electronic

#### Light output tolerance +/- 10%





















# 8141523




# NIU LED RSYM CL.II 4500 GR.

#### **PHOTOMETRIC DATA:**







# **Product datasheet**

# NIU



# ACCESORIES : Assembly



Product code:

Description:

9600353 NIU ACC. Ø76 POLE ADAPTER