Product datasheet

NIU



8141563



NIU LED STREET CL.II 4500 GR.

Description:

Urban luminaire NIU LED STREET CL.II 4500 GR., LAMP brand. Made of texturised grey lacquered aluminium injection and flat tempered serigraphed glass. Model for HI-POWER LED with neutral white colour temperature and control gear included. With street optics. IP66, IK10 protection rating. Insulation class II. To adapt to Ø60mm.



Finish: Texturised grey

Weight: 12.450~g Maximum surface exposed to wind: 0.18~M2

Installation: Integrated in light-pole

TECHNICAL SPECIFICATIONS:

 Light output:
 3.439 lm
 oK:
 4000

 Plum:
 52W
 CRI:
 70

Efficacy: 66,1 lm/w

Type: HI POWER CREE MacAdam:

LED Lifetime: 50.000 L90 **Power Supply**: 220-240V 50/60Hz

Power: 48W Gear: Electronic

Light output tolerance +/- 10%


















8141563 NIU LED STREET CL.II 4500 GR.



PHOTOMETRIC DATA:







Product datasheet

NIU



ACCESORIES:

Assembly



Product code:

9600313



Product code: 9600353

de: Descriptio

Description:

NIU ACC. Ø76 POLE ADAPTER

ACCESORIES:

Support



Froduct co

9600323



NIU ACC. IND Ø60 ARM

NIU ACC. IND Ø60-135 POLE CLAMP



Product code:

9600333 9600343

Description:

NIU ACC. Ø48 POLE BRACKET NIU ACC. Ø60 POLE BRACKET



Product code:

9600363

Description:

NIU ACC. WALL ARM