Product datasheet

KOMBIC 200




9241361



KOMBIC MATT 3000 NW

Description:

Round recessed downlight model KOMBIC MATT 3000 NW, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and matt metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for COB LED, with neutral white colour temperature and control gear included. IP44 protection rating. Insulation class II. Photogiological safety group 0. Photobiological safety group 0.



Finish: Shiny white RAL 9010

Weight: 976 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 2.084 lm
 °K:
 4000

 Plum:
 18,1W
 CRI:
 80

 Efficacy:
 115,1 lm/w
 MacAdam:
 3

Type: COB TRIDONIC Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 Gear: Electronic

Power: 17W

Light output tolerance +/- 10%


























KOMBIC 200




9241361

KOMBIC MATT 3000 NW

PHOTOMETRIC DATA:







	H (m)	D (m)	Emax	Emed
	1	1,61	1334	676
	2	3,22	334	169
	3	4,84	148	75
	4	6,45	83	42

Product datasheet

KOMBIC 200



ACCESORIES:

Optical



Product code: Description:

8606140 DOMO 220/KOMBIC ACC.TRANSP GLASS WH.
8606143 DOMO 220/KOMBIC ACC.TRANSP GLASS GR.



Product code:

8606142

Description:

DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

9200210 DOMO 220/KOMBIC ACC. DECO RING WH.
9200213 DOMO 220/KOMBIC ACC. DECO RING GR.



Product code:

9200212

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

Description:

9200220 KOMBIC ACC. Ø250 ADAPTER RING WH.

KOMBIC 200



