Product datasheet

KOMBIC 200

9241520



KOMBIC 200 RD 5000 IP40 WW OPAL BR/WH

Description:

Round recessed downlight model KOMBIC 200 RD 5000 IP40 WW OPAL BR/WH, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for COB LED, with warm white colour temperature and control gear included. IP44 protection rating. Insulation class II.

Shiny white RAL 9010 Finish:

Weight: 1.536 g



Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.735 lm °K: 3000 Plum: 39W CRI: 80 Efficacy: 95,8 lm/w MacAdam: 3

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 Gear: Electronic

36W Power:

Light output tolerance +/- 10%




























KOMBIC 200




9241520

KOMBIC 200 RD 5000 IP40 WW OPAL BR/WH

PHOTOMETRIC DATA:





alpha = 53,6°	H (m)	D (m)	Emax	Emed
	1	1,01	3643	2297
	2	2,02	911	574
	3	3,03	405	255
	4	4,04	228	144

Product datasheet

KOMBIC 200



ACCESORIES:

Optical



Product code: Description:

8606140 DOMO 220/KOMBIC ACC.TRANSP GLASS WH.
8606143 DOMO 220/KOMBIC ACC.TRANSP GLASS GR.



Product code:

8606142

Description:

DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

9200210 DOMO 220/KOMBIC ACC. DECO RING WH.
9200213 DOMO 220/KOMBIC ACC. DECO RING GR.



Product code:

9200212

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

Description:

9200220 KOMBIC ACC. Ø250 ADAPTER RING WH.

KOMBIC 200



