Product datasheet

KOMBIC 200

9241560



KOMBIC 200 SQ 5000 IP40 WW OPAL BR/WH


Description:

Square recessed downlight model KOMBIC 200 SQ 5000 IP40 WW OPAL BR/WH, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for COB LED, with warm white colour temperature and control gear included. IP44 protection rating. Insulation class II.

Shiny white RAL 9010 Finish:

Weight: 1.536 g

Installation: Recessed



TECHNICAL SPECIFICATIONS:

Light output: 3.249 Im °K: 3000 Plum: 39W CRI: 80 Efficacy: 83,3 lm/w MacAdam: 3

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L70 B10 Gear: Electronic

36W Power:

Light output tolerance +/- 10%




































KOMBIC 200





9241560

KOMBIC 200 SQ 5000 IP40 WW OPAL BR/WH

PHOTOMETRIC DATA:







_					
	H (m)	D (m)	Emax	Emed	
	1	2,02	1728	745	
	2	4,04	432	186	
	3	6,06	192	83	
	4	8,08	108	47	

Product datasheet

KOMBIC 200



ACCESORIES:

Assembly



Product code: Description:

9000163 DOMO SQ/KOMBIC SQ ACC. REC BOX


ACCESORIES:

Optical



Product code: Description: Product code: Description:

9006140 DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH. 9006142 DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK.



Product code: Description: Product code: Description:

9006200 DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH. 9006202 DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK.