Product datasheet

RING


9251510



RING THINNER FRAME SQ 1000 WW MFL DIM WH

Description:

Fixed individual square downlight model RING THINNER FRAME SQ 1000 WW MFL DIM WH., LAMP brand. Made of white-lacquered aluminium. With a very thin frame. Model for COB LED, warm white color temperature. Medium Flood high-purity faceted aluminium reflector. High visual comfort thanks to the non-flushed position of the lamp. Insulation class II. Electronic equipment incorporated.



Finish: Matte white RAL 9010

Weight: 264 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 971 lm °K: 3000 Plum: 11,8W CRI: 80 Efficacy: 82,3 lm/w 3 MacAdam:

Type: COB HONGLITRONIC Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L70 Gear: Adjustable TRIAC

10W Power:

Light output tolerance +/- 10%
























RING






RING THINNER FRAME SQ 1000 WW MFL DIM WH

PHOTOMETRIC DATA:





alpha = 28,2°	H (m)	D (m)	Emax	Emed
\bigwedge	1	0,50	3041	2096
	2	1,00	760	524
	3	1,51	338	233
	4	2,01	190	131

RING



