Product datasheet

KOMBIC 200


9281450



KOMBIC 200 SQ 4000 IP40 WW OPAL DA BR/WH

Description:

Square recessed downlight model KOMBIC SQ 4000 WW, LAMP brand. Interior diffuser made of opal polycarbonate specially for LED, injection aluminium dissipator and torkit type easy-fit fastening system. Model for MID-POWER LED, with warm white colour temperature and control gear included. IP44 protection rating. Insulation class II.



Finish: Shiny white RAL 9010

Weight: 822 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.024 lm °K: 3000 Plum: 25,4W CRI: 80 Efficacy: 79,7 lm/w MacAdam: 3

Type: MID POWER TRIDONIC Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B10 Gear: Adjustable DALI

24W Power:

Light output tolerance +/- 10%



























+34937366800

Tel.


KOMBIC 200





9281450

KOMBIC 200 SQ 4000 IP40 WW OPAL DA BR/WH

PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed
1	2,02	1077	464
2	4,04	269	116
3	6,06	120	52
4	8,08	67	29

Product datasheet

KOMBIC 200



ACCESORIES:

Assembly



Product code: Description:

9000163 DOMO SQ/KOMBIC SQ ACC. REC BOX


ACCESORIES:

Optical



Product code: Description: Product code: Description:

9006140 DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH. 9006142 DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK.



Product code: Description: Product code: Description:

9006200 DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH. 9006202 DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK.