Product datasheet

KOMBIC 200


9281460



KOMBIC 200 SQ 4000 IP40 NW OPAL DA BR/WH

Description:

Square recessed downlight model KOMBIC SQ 4000 NW, LAMP brand. Interior diffuser made of opal polycarbonate specially for LED, injection aluminium dissipator and torkit type easy-fit fastening system. Model for MID-POWER LED, with neutral white colour temperature and control gear included. IP44 protection rating. Insulation class II.



Finish: Shiny white RAL 9010

Weight: 822 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.131 lm °K: 4000 Plum: 25,4W CRI: 80

Efficacy: 83,9 lm/w

Type: MID POWER TRIDONIC MacAdam: 3

LED Lifetime: 50.000 L80 B10 Power Supply: 220-240V 50/60Hz 24W Gear: Power: Adjustable DALI

Light output tolerance +/- 10%
































KOMBIC 200




9281460

KOMBIC 200 SQ 4000 IP40 NW OPAL DA BR/WH

PHOTOMETRIC DATA:





alpha = 90,6°	H (m)	D (m)	Emax	Emed
	1	2,02	1134	489
	2	4,04	284	122
	3	6,06	126	54
	4	8,08	71	31

Product datasheet

KOMBIC 200



ACCESORIES:

Assembly



Product code: Description:

9000163 DOMO SQ/KOMBIC SQ ACC. REC BOX


ACCESORIES:

Optical



Product code: Description: Product code: Description:

9006140 DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS WH. 9006142 DOMO SQ/KOMBIC SQ ACC. TRANSP GLASS BK.



Product code: Description: Product code: Description:

9006200 DOMO SQ/KOMBIC SQ ACC. DECO FRAME WH. 9006202 DOMO SQ/KOMBIC SQ ACC. DECO FRAME BK.