Product datasheet

KOMBIC 200



9281531



KOMBIC 200 RD 5000 IP40 NW OPAL DA MA/WH

Description:

Finish: Shiny white RAL 9010

Weight: 1.536 g



Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.845 lm °K: 4000 Plum: 39W CRI: 80 Efficacy: 98,6 lm/w MacAdam: 3

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L70 B10 Gear: Adjustable DALI

Power: 36W

Light output tolerance +/- 10%


























KOMBIC 200







KOMBIC 200 RD 5000 IP40 NW OPAL DA MA/WH

PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed
1	1,61	2461	1247
2	3,22	615	312
3	4,84	273	139
4	6,45	154	78

Product datasheet

KOMBIC 200



ACCESORIES:

Optical



Product code: Description:

8606140 DOMO 220/KOMBIC ACC.TRANSP GLASS WH.
8606143 DOMO 220/KOMBIC ACC.TRANSP GLASS GR.



Product code:

8606142

Description:

DOMO 220/KOMBIC ACC.TRANSP GLASS BK.



Product code:

Description:

9200210 DOMO 220/KOMBIC ACC. DECO RING WH.
9200213 DOMO 220/KOMBIC ACC. DECO RING GR.



Product code:

9200212

Description:

DOMO 220/KOMBIC ACC. DECO RING BK.



Product code:

Description:

9200220 KOMBIC ACC. Ø250 ADAPTER RING WH.

KOMBIC 200



