Product datasheet

AMBIENT

Worktitude for light


AM1WM07015830NG



AMBIENT LED 700MM 2600 WW GR.

Description:

Wall-washing luminaire with direct and indirect light to mount to walls or ceilings model AMBIENT LED 700MM, LAMP brand. Made of aluminium extrusion and glazed polycarbonate diffuser. Model for MID-POWER LED, 3000K colour temperature, CRI80 and control gear included. IP40, IK06 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and grey.



Finish: Gloss grey

Dimensions: 700 x 75 x 108 mm **Weight:** 1.656 g

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

 Light output:
 1.950 lm
 °K:
 3000

 Plum:
 18,8W
 CRI:
 80

 Efficacy:
 103,7 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 16W

Light output tolerance +/- 10%



















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
















AMBIENT








PHOTOMETRIC DATA:

8840203 η = 100% Imax = 216 cd/klm UTE: 0,50D + 0,50T CIE: 56 85 100 50 100



AMBIENT



