#### **Product datasheet**

#### **AMBIENT**

# LAMP Worktitude for light


### AM1WM07015840NW



### AMBIENT LED 700MM 2600 NW WH.

### Description:

Wall-washing luminaire with direct and indirect light to mount to walls or ceilings model AMBIENT LED 700MM, LAMP brand. Made of aluminium extrusion and glazed polycarbonate diffuser. Model for MID-POWER LED, 4000K colour temperature, CRI80 and control gear included. IP40, IK06 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and grey.



Finish: Matte white RAL 9010

**Dimensions**: 700 x 75 x 108 mm **Weight**: 1.656 g

Installation: Wall mounted

### **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.030 lm
 % :
 4000

 Plum:
 18,8W
 CRI :
 80

 Efficacy:
 108 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 16W

## Light output tolerance +/- 10%



















# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU
















## **AMBIENT**








### **PHOTOMETRIC DATA:**

8841200 η = 100% Imax = 216 cd/klm UTE: 0,50D + 0,50T CIE: 56 85 100 50 100



# **AMBIENT**



