Product datasheet

AMBIENT


AM1WM13015840NG



AMBIENT LED 1300MM 5200 NW GR.

Description:

Wall-washing luminaire with direct and indirect light to mount to walls or ceilings model AMBIENT LED 1300MM, LAMP brand. Made of aluminium extrusion and glazed polycarbonate diffuser. Model for MID-POWER LED, 4000K colour temperature, CRI80 and control gear included. IP40, IK06 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and grey.



Finish: Gloss grey Dimensions: 1.300 x 75 x 108 mm

Weight: 2.992 g

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

Light output:	4.060 lm	⁰K :	4000
Plum:	35,1W	CRI :	80
Efficacy:	115,7 lm/w	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	Gear:	Electronic
Power:	31W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

AMBIENT


8841213 η = 100%

AM1WM13015840NG

AMBIENT LED 1300MM 5200 NW GR.



Imax = 216 cd/klm UTE: 0,50D + 0,50T





AMBIENT



