Product datasheet

AMBIENT




AM1WM13015840NW



AMBIENT LED 1300MM 5200 NW WH.

Description:

Wall-washing luminaire with direct and indirect light to mount to walls or ceilings model AMBIENT LED 1300MM, LAMP brand. Made of aluminium extrusion and glazed polycarbonate diffuser. Model for MID-POWER LED, 4000K colour temperature, CRI80 and control gear included. IP40, IK06 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and grey.



Finish: Matte white RAL 9010

Dimensions: 1.300 x 75 x 108 mm **Weight**: 2.992 g

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

 Light output:
 4.060 lm
 °K:
 4000

 Plum:
 35,1W
 CRI:
 80

 Efficacy:
 115,7 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 31W

Light output tolerance +/- 10%



















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















AMBIENT








PHOTOMETRIC DATA:

8841210 η = 100% Imax = 216 cd/klm UTE: 0,50D + 0,50T CIE: 56 85 100 50 100



AMBIENT



