

AM2060DIMOOO840NW



AMBIENT G2 LC 600 D/I NW OP/OP WH

Description:

LAMP surface wall mounted system AMBIENT G2 LC 600 D/I. Manufactured from extruded aluminum with an 75% recycling rate with Opal polycarbonate diffusers. Model for LED MID-POWER, colour temperature 4000K and IRC80. Electronic ON OFF gear included. IP40, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: >72.000 L80B10. Available luminaire body finishes: White and black. Frontal accessory sold separately with the desired finish. White, Black, Raw o Anodised (Gold, Bronze, Champagne, Blue and Black).

Finish: Matte white RAL 9010 600 x 80 x 48 mm Dimensions:

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

Light output: 2.077 lm °K: 4000 Plum: 18,6W CRI: 80 Efficacy: 111,7 lm/w 3 MacAdam:

Type: MID POWER Power Supply: 220-240V 50/60Hz

LED Lifetime: >72.000 L80B10 (Ta=25°C) Gear: Electronic

Power: 16W

Light output tolerance +/- 10%



CLASE

























CUSTOM MADE OPTIONS:























AM2060DIMOOO840NW


AMBIENT G2 LC 600 D/I NW OP/OP WH

PHOTOMETRIC DATA:

AM2060DIMOOO840NW η = 100% Imax = 188 cd/klm UTE: 0,50E + 0,50T Imax CIE: 49 81 97 50 100









ACCESORIES:

Assembly



Product code: AM2AC060ABK



AMBIENT G2 ACC FRONT END 600 AN. BLACK



Product code: AM2AC060ABL

Description:

AMBIENT G2 ACC FRONT END 600 AN. BLUE



AM2AC060ABZ

Description: Product code:

AMBIENT G2 ACC FRONT END 600 AN. BRONZE



AM2AC060ACH

Description:

AMBIENT G2 ACC FRONT END 600 AN. CHAMP



Product code: AM2AC060AGD

Description: AMBIENT G2 ACC FRONT END 600 AN. GOLD



Product code: AM2AC060ARW

Description:

AMBIENT G2 ACC FRONT END 600 AL RAW



Product code:

AM2AC060B AMBIENT G2 ACC FRONT END 600MM BK



Product code: AM2AC060W

Description:

AMBIENT G2 ACC FRONT END 600MM WH



Product code:

AM2ACECB AMBIENT G2 ACC END COVER BK

Description:

Description:



Product code:

AM2ACECW

Description:

AMBIENT G2 ACC END COVER WH

Data according to regulations 2019/2020/EU and 2019/2015/EU