Product datasheet

AMBIENT



AM2120DI25OO8TWDB



AMBIENT G2 IND 1200 D/I TW O/O DA BK

Description:

LAMP surface wall mounted fixture AMBIENT G2 IND 1200 D/I. Manufactured from extruded aluminum with an 75% recycling rate with Opal polycarbonate diffusers. Model for LED MID-POWER, colour temperature Tunnable White and IRC80. Electronic ON OFF gear included. IP40, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90B10. Available luminaire body finishes: White and black. Frontal accessory sold separately with the desired finish. White, Black, Raw o Anodised (Gold, Bronze, Champagne, Blue and Black).



Finish: Matte white RAL 9010 1.200 x 80 x 48 mm Dimensions:

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

Light output: 3.964 Im TUNNABLE WHI °K:

Plum: 31,9W CRI: 80 Efficacy: 124,3 lm/w 3 MacAdam:

Type: MID POWER Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L90B10 (Ta=25°C) Gear: Adjustable DALI

28W Power:

Light output tolerance +/- 10%



CLASE



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













AMBIENT





AM2120DI25OO8TWDB


AMBIENT G2 IND 1200 D/I TW O/O DA BK

PHOTOMETRIC DATA:

AM2120DI25OO8TWDB $\eta = 100\%$ Imax = 188 cd/klm UTE: 0,50E + 0,50T CIE: 49 81 97 50 100







AMBIENT



ACCESORIES: Assembly



Product code: AM2ACIN120ABK



AMBIENT G2 ACC FRONT IND 1200 AN. BLACK



AM2ACIN120ABL

Description: AMBIENT G2 ACC FRONT IND 1200 AN. BLUE



Product code: AM2ACIN120ABZ

Description: Product code:

AMBIENT G2 ACC FRONT IND 1200 AN. BRONZE



AM2ACIN120ACH

Description: AMBIENT G2 ACC FRONT IND 1200 AN. CHAMP



Product code: AM2ACIN120AGD



AMBIENT G2 ACC FRONT IND 1200 AN. GOLD



AM2ACIN120ARW

Description:

AMBIENT G2 ACC FRONT IND 1200 AL RAW



Product code: AM2ACIN120B

Description:

AMBIENT G2 ACC FRONT IND 1200MM BK



Product code:

AM2ACIN120W

Description:

AMBIENT G2 ACC FRONT IND 1200MM WH

Data according to regulations 2019/2020/EU and 2019/2015/EU