Product datasheet

AMBIENT



AM2120DS25AG840DB



AMBIENT G2 IND 1200 D/I D NW A/G DA B

Description:

LAMP surface wall mounted fixture AMBIENT G2 IND 1200 D/I Double Switch. Manufactured from extruded aluminum with an 75% recycling rate with Asymetric polycarbonate optic and Grazer polycarbonate optic. Model for LED MID-POWER, colour temperature 4000K and IRC80. Electronic DALI gear included. IP40, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: >72.000 L80B10. Available luminaire body finishes: White and black. Frontal accessory sold separately with the desired finish. White, Black, Raw o Anodised (Gold, Bronze, Champagne, Blue and Black).



Finish: Matte black RAL 9011

Dimensions: 1.200 x 80 x 48 mm

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

 Light output:
 6.458 lm
 °K:
 4000

 Plum:
 48W
 CRI:
 80

 Efficacy:
 134,5 lm/w
 MacAdam:
 3

 Type:
 MID POWER
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 >72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 42W

Light output tolerance +/- 10%



CLASE

















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













AMBIENT








PHOTOMETRIC DATA:

AM2120DS25AG840DB

AM2120DS25AG840DB $\eta = 100\%$ lmax = 542 cd/klmUTE: 0,36D + 0,65T CIE: 53 84 98 35 100







AMBIENT



ACCESORIES: Assembly



Product code: AM2ACIN120ABK



AMBIENT G2 ACC FRONT IND 1200 AN. BLACK



AM2ACIN120ABL

Description: AMBIENT G2 ACC FRONT IND 1200 AN. BLUE



Product code: AM2ACIN120ABZ

Description: Product code:

AMBIENT G2 ACC FRONT IND 1200 AN. BRONZE



AM2ACIN120ACH

Description: AMBIENT G2 ACC FRONT IND 1200 AN. CHAMP



Product code: AM2ACIN120AGD



AMBIENT G2 ACC FRONT IND 1200 AN. GOLD



AM2ACIN120ARW

Description:

AMBIENT G2 ACC FRONT IND 1200 AL RAW



Product code: AM2ACIN120B

Description:

AMBIENT G2 ACC FRONT IND 1200MM BK



Product code:

AM2ACIN120W

Description:

AMBIENT G2 ACC FRONT IND 1200MM WH

Data according to regulations 2019/2020/EU and 2019/2015/EU