Product datasheet

AMBIENT



AM2120DS250O830DW



Description:

AMBIENT G2 IND 1200 D/I D WW OP/OP DA W

LAMP surface wall mounted fixture AMBIENT G2 IND 1200 D/I Double Switch. Manufactured from extruded aluminum with an 75% recycling rate with Opal polycarbonate diffusers. Model for LED MID-POWER, colour temperature 3000K and IRC80. Electronic DALI gear included. IP40, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: >72.000 L80B10. Available luminaire body finishes: White and black. Frontal accessory sold separately with the desired finish. White, Black, Raw o Anodised (Gold, Bronze, Champagne, Blue and Black).



Finish: Matte white RAL 9010 1.200 x 80 x 48 mm Dimensions:

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

Light output: 3.960 lm °K: 3000 Plum: 34,5W CRI: 80 Efficacy: 114,8 lm/w 3 MacAdam:

Type: MID POWER Power Supply: 220-240V 50/60Hz LED Lifetime: >72.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

Power: 32W

Light output tolerance +/- 10%



CLASE

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













AMBIENT








AMBIENT G2 IND 1200 D/I D WW OP/OP DA W

PHOTOMETRIC DATA:

AM2120DS25OO830DW η = 100% Imax = 188 cd/kIm UTE: 0,50E + 0,50T CIE: 49 81 97 50 100







Data according to regulations 2019/2020/EU and 2019/2015/EU

AMBIENT



ACCESORIES: Assembly



Product code: AM2ACIN120ABK



AMBIENT G2 ACC FRONT IND 1200 AN. BLACK



AM2ACIN120ABL

Description: AMBIENT G2 ACC FRONT IND 1200 AN. BLUE



Product code: AM2ACIN120ABZ

Description: Product code:

AMBIENT G2 ACC FRONT IND 1200 AN. BRONZE



AM2ACIN120ACH

Description: AMBIENT G2 ACC FRONT IND 1200 AN. CHAMP



Product code: AM2ACIN120AGD



AMBIENT G2 ACC FRONT IND 1200 AN. GOLD



AM2ACIN120ARW

Description:

AMBIENT G2 ACC FRONT IND 1200 AL RAW



Product code: AM2ACIN120B

Description:

AMBIENT G2 ACC FRONT IND 1200MM BK



Product code:

AM2ACIN120W

Description:

AMBIENT G2 ACC FRONT IND 1200MM WH

Data according to regulations 2019/2020/EU and 2019/2015/EU