BAULINE


BA3RE068MOEL840NG



BAULINE G3 REC 679MM 2500 NW ELLI AND

Description:

Outdoor recessed structure model BAULINE G2 REC 2500 NW MFL, LAMP brand. Made of silver anodized aluminum extrusion and end covers of aluminum injection lacquered in silver grey polyester, with AISI304 stainless steel frame and serigraphed tempered glass. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Elliptical optics. IP67, IK10 protection rating. Insulation class I. Lifetime: 83.000 L90 B10



Finish: Anodized matte silver

Dimensions: 679 x 80 x 100 mm Weight: 3.302 g

Installation: Floor recessed

683 x 72 x 107 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 1.916 lm °K: 4000 Plum: 16,2W CRI: 80 Efficacy: 118,3 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 83.000 L90 B10 (Ta=25°C) Gear: Electronic

15,4W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:



























BAULINE





BA3RE068MOEL840NG


BAULINE G3 REC 679MM 2500 NW ELLI AND

PHOTOMETRIC DATA:

BA3RE068MOEL840NG η = 100% Imax = 2563 cd/klm UTE: 1,00T CIE: 0 0 0 0 100







Product datasheet

BAULINE



ACCESORIES: **Assembly**



Product code: BUREBO0683

Description:

BAULINE ACC. REC BOX 683



Product code: BUREBO1272

Description:

BAULINE ACC. REC BOX 1272