BAULINE


BA3RE068MOMF830NG



BAULINE G3 REC 679MM 2500 WW MFL AND

Description:

Outdoor recessed structure model BAULINE G3 REC 679MM 2500 WW MFL, LAMP brand. Made of silver anodized aluminum extrusion and end covers of aluminum injection lacquered in silver grey polyester, with AISI304 stainless steel frame and serigraphed tempered glass. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP67, IK10 protection rating. Insulation class I. Lifetime: 83.000 L90 B10



Finish: Anodized matte silver

Dimensions: 679 x 80 x 100 mm Weight: 3.302 g

Installation: Floor recessed

683 x 72 x 107 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 1.996 lm °K: 3000 Plum: 16,2W CRI: 80 Efficacy: 123,2 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 83.000 L90 B10 (Ta=25°C) Gear: Electronic

15,4W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:



























BAULINE








PHOTOMETRIC DATA:

BA3RE068MOMF830NG

BA3RE068MOMF830NG η = 100% Imax = 4407 cd/klm UTE: 1,00T CIE: 0 0 0 0 100







Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

BAULINE



ACCESORIES: **Assembly**



Product code: BUREBO0683

Description:

BAULINE ACC. REC BOX 683



Product code: BUREBO1272

Description:

BAULINE ACC. REC BOX 1272