BAULINE


BA3RE127MOEL830NG



BAULINE G3 REC 1268MM 5000 WW ELLI AND

Description:

Outdoor recessed structure model BAULINE G3 REC 1268MM 5000 WW ELLI, LAMP brand. Made of silver anodized aluminum extrusion and end covers of aluminum injection lacquered in silver grey polyester, with AISI304 stainless steel frame and serigraphed tempered glass. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Elliptical optics. IP67, IK10 protection rating. Insulation class I. Lifetime: 83.000 L90 B10



Finish: Anodized matte silver

1.268 x 80 x 100 mm Dimensions: Weight: 5.510 g

Installation: Floor recessed

1,272 x 72 x 107 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 3.832 lm °K: 3000 Plum: 32,3W CRI: 80 Efficacy: 118,6 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 83.000 L90 B10 (Ta=25°C) Gear: Electronic

30,8W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:



























BAULINE





BA3RE127MOEL830NG


BAULINE G3 REC 1268MM 5000 WW ELLI AND

PHOTOMETRIC DATA:

BA3RE127MOEL830NG $\eta = 100\%$ $Imax = 2563 \ cd/klm$ $UTE: \ 1,00T$ $CIE: \ 0 \ 0 \ 0 \ 100$







Product datasheet

BAULINE



ACCESORIES: **Assembly**



Product code: BUREBO0683

Description:

BAULINE ACC. REC BOX 683



Product code: BUREBO1272

Description:

BAULINE ACC. REC BOX 1272