BAULINE


BA3SF065MOMF840NG



BAULINE G3 SUR 650MM 2500 NW MFL AND

Description:

Outdoor suspended or mounted surface structure model BAULINE G3 SUR 650MM 2500 NW MFL, LAMP brand. Made of silver anodized aluminum extrusion and end covers of lacquered aluminum injection lacquered in silver grey polyester, with decorative frontal piece of silver serigraph polycarbonate. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP67, IK10 protection rating. Insulation class I. Lifetime: 83.000 L90 B10





Finish: Anodized matte silver Dimensions: 650 x 50 x 95 mm

Weight: 2.252 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.972 lm °K: 4000 Plum: 16,2W CRI: 80 Efficacy: 121,7 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 83.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 15,4W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















BAULINE






PHOTOMETRIC DATA:


BA3SF065MOMF840NG η = 100%


Imax = 4407 cd/klm


UTE: 1,00A

CIE: 93 100 100 100 100









Product datasheet

BAULINE



ACCESORIES:

Support



Product code:

WAAR120G

Description:

ACC. ADJ WALL ARM 120 GR.



Product code:

WAAR380G

Description:

ACC. ADJ WALL ARM 380 GR.