BAULINE


BA3SF124MOSP840NG



BAULINE G3 SUR 1240MM 5000 NW SP AND

Description:

Outdoor suspended or mounted surface structure model BAULINE G3 SUR 1240MM 5000 NW SP, LAMP brand. Made of silver anodized aluminum extrusion and end covers of lacquered aluminum injection lacquered in silver grey polyester, with decorative frontal piece of silver serigraph polycarbonate. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP67, IK10 protection rating. Insulation class I. Lifetime: 83.000 L90 B10





Finish: Anodized matte silver

1.240 x 50 x 95 mm Dimensions: Weight: 3.380 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 3.873 lm °K: 4000 Plum: 32,3W CRI: 80 Efficacy: 119,9 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 83.000 L90 B10 (Ta=25°C) Gear: Electronic

30,8W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:



























BAULINE



BA3SF124MOSP840NG

BAULINE G3 SUR 1240MM 5000 NW SP AND

PHOTOMETRIC DATA:


BA3SF124MOSP840NG η = 100%


lmax = 8284 cd/klm


UTE: 1,00A

CIE: 93 100 100 100 100









Product datasheet

BAULINE



ACCESORIES:

Support



Product code:

WAAR120G

Description:

ACC. ADJ WALL ARM 120 GR.



Product code:

WAAR380G

Description:

ACC. ADJ WALL ARM 380 GR.