#### **Product datasheet**

# **B-SIDE LED**

### BS1DB4503840NA




#### B-SIDE LED 450 250 NW ANT.

#### **Description:**

Finish:

Dimensions:

Bollard model B-SIDE LED 450 250, LAMP brand. Made in extruded recycled aluminum with a rate of 80% and injection, and translucent polycarbonate diffuser. 450mm in height. Its base has an anti-corrosion electro coating treatment. Model for HI-POWER LED, with 4000K colour temperature, CRI 80 and control gear included. IP65, IK10 protection rating. Insulation class I. Lifetime: 50. 000 L70 B10. BUG Rate: B0 U1 G0, ULOR: 1%. Available finishes: anthracite and textured grey.



a 160

Installation: Standing

#### **TECHNICAL SPECIFICATIONS:**


Textured anthracite

Ø 160 mm x 450 mm

Light output:	112 lm	⁰К:	4000
Plum:	4,5W	CRI :	80
Efficacy:	24,8 lm/w	Power Supply:	110-240V 50/60Hz
Туре:	HIGH POWER LED	Gear:	Electronic
LED Lifetime:	50.000 L70 B10 (Ta=25⁰C)		
Power:	2.4W		

Weight: 2.794 g

#### Light output tolerance +/- 10%



### CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light


## **B-SIDE LED**

5841164 **η = 24%** 

BS1DB4503840NA

B-SIDE LED 450 250 NW ANT.







Product datasheet

**B-SIDE LED** 







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es