Product datasheet

B-SIDE LED

BS1DB4503840NG



450 mm

a 160

B-SIDE LED 450 250 NW GR.

Description:

Bollard model B-SIDE LED 450 250, LAMP brand. Made in extruded recycled aluminum with a rate of 80% and injection, and translucent polycarbonate diffuser. 450mm in height. Its base has an anti-corrosion electro coating treatment. Model for HI-POWER LED, with 4000K colour temperature, CRI 80 and control gear included. IP65, IK10 protection rating. Insulation class I. Lifetime: 50. 000 L70 B10. BUG Rate: B0 U1 G0, ULOR: 1%. Available finishes: anthracite and textured grey.


| Finish: T | exturised grey | |
|-------------|-------------------|-----------------|
| Dimensions: | Ø 160 mm x 450 mm | Weight: 2.794 g |

Installation: Standing

TECHNICAL SPECIFICATIONS:

| Light output: | 112 lm | ⁰К: | 4000 |
|---------------|--------------------------|---------------|------------------|
| Plum: | 4,5W | CRI : | 80 |
| Efficacy: | 24,8 lm/w | Power Supply: | 110-240V 50/60Hz |
| Туре: | HIGH POWER LED | Gear: | Electronic |
| LED Lifetime: | 50.000 L70 B10 (Ta=25ºC) | | |
| Power: | 2.4W | | |

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light


B-SIDE LED

5841163 **η = 24%**

BS1DB4503840NG

B-SIDE LED 450 250 NW GR.







Product datasheet

B-SIDE LED







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es