
Product datasheet

B-SIDE LED

BS1DB8505840NA

850 mm





Description:

Bollard model B-SIDE LED 850 500, LAMP brand. Made in extruded recycled aluminum with a rate of 85,4% and injection, and translucent polycarbonate diffuser. 850mm in height. Its base has an anti-corrosion electro coating treatment. Model for HI-POWER LED, with 4000K colour temperature, CRI 80 and control gear included. IP65, IK10 protection rating. Insulation class I. Lifetime: 50. 000 L90. BUG Rate: B0 U1 G0, ULOR: 5,4%. Available finishes: anthracite and textured grey.


Finish:	Textured anthracite		
Dimensior	is: Ø 160 mm x 850 mm	Weight: 4.450 g	J

Installation: Standing

TECHNICAL SPECIFICATIONS:

Light output:	171 lm	⁰K :	4000
Plum:	6,4W	CRI :	80
Efficacy:	26,7 lm/w	MacAdam:	4
Туре:	HIGH POWER LED	Power Supply:	110-240V 50/60Hz
LED Lifetime:	50.000 L90 (Ta=25°C)	Gear:	Electronic
Power:	4.8W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

B-SIDE LED


5841074 η = 100%

BS1DB8505840NA

B-SIDE LED 850 500 NW ANT.



Imax = 1014 cd/klm UTE: 0,95C + 0,06T





Product datasheet

B-SIDE LED







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es