B-SIDE LED

BS1DB8505840NG



B-SIDE LED 850 500 NW GR.

Description:

Bollard model B-SIDE LED 850 500, LAMP brand. Made in extruded recycled aluminum with a rate of 85,4% and injection, and translucent polycarbonate diffuser. 850mm in height. Its base has an anti-corrosion electro coating treatment. Model for HI-POWER LED, with 4000K colour temperature, CRI 80 and control gear included. IP65, IK10 protection rating. Insulation class I. Lifetime: 50. 000 L90. BUG Rate: B0 U1 G0, ULOR: 5,4%. Available finishes: anthracite and textured grey.

Finish: Texturised grey

Dimensions: Ø 160 mm x 850 mm Weight: 4.450 g

Installation: Standing



TECHNICAL SPECIFICATIONS:

Light output: 171 lm °K: 4000 Plum: 6,4W CRI: 80 Efficacy: 26,7 lm/w 4 MacAdam:

Type: HIGH POWER LED Power Supply: 110-240V 50/60Hz

LED Lifetime: 50.000 L90 (Ta=25°C) Gear: Electronic

4.8W Power:

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU







B-SIDE LED




BS1DB8505840NG

B-SIDE LED 850 500 NW GR.

PHOTOMETRIC DATA:

 $_{\eta}$ = 100% Imax = 1014 cd/klm UTE: 0,95C + 0,06T CIE: 64 92 99 94 100



B-SIDE LED





